

## MIKASA® TAMPING RAMMER DIESEL MTX-85DYC

Mikasa® Tamping Rammers are perfectly balanced to deliver hard hitting compaction while ensuring operator comfort through reduce noise and low Vibration Absorbing System handle.

### Cyclonic air filtration system

- For superior air filtration to lengthen service internals and improve engine protection.



### Central lifting hook

- Easy and safe onsite handling

### Handle roller

- Easy loading into vehicles and the unit can also lie down to 90° for transport.

### Fully integrated control switch

- Controls On / Off switch, Fuel Tap and Engine Throttle



### Low vibration handles

- Vibration Absorbing System for reduced hand and arm vibration transfer to the operator.

### Engine Guard

- Fully protected engine to eliminate damage to critical engine components.



### Yanmar diesel engine

- Provides hassle free operation and low fuel consumption and low engine emissions.



# PRODUCT & PERFORMANCE SPECIFICATIONS



## MIKASA® TAMPING RAMMERS



MTX-60E



MTX-70E




MTX-85DYC

Model	Operating Weight (kg)	Shoe Size (w x l) (mm)	Jumping Stroke (mm)	Impact Rate (blows/m)	Impact Force (Max) (kN)	Average Travel Speed* (m/min)	Compaction Depth* (cm)	Engine Make & Model	Max Rated Power (Hp)	Average HAV (m/s <sup>2</sup> )	Fuel Type	Fuel Tank Capacity (L)	Product Code
MTX-60E	64	265 x 340	50-80	644-695	13.6	10-12	50-85	Honda GX100	3	5.2	P	2.5	FT2TX60E-UNIT
MTX-70E	75	285 x 340	50-80	644-695	14.9	10-12	45-70	Honda GX100	3	5.6	P	3	FT2MTX70-UNIT
MTX-85DYC	93	285 x 340	50-80	656-698	15.7	10-12	50-85	Yanmar L48N	4.7	18.5	D	3.3	FT285DYC-UNIT

## WHEEL KIT

Product Code	Operating Weight (kg)	Suits	Wheel Diametre (mm)	Wheel Type
FT201692-UNIT	11	MTX Series Rammers	260	Solid Flat Free Urethane



Replacement Shoe  
NPS70430-UNIT



Trenching Shoe  
(115mm wide x 330mm high)  
NPS51919-UNIT



Trenching Shoe  
(165mm wide x 330mm high)  
NPS51931-UNIT

EXCLUSIVE TO



This Technical Data Sheet (TDS) summarises our best knowledge of the product, based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used. Our responsibility for products sold is subject to our standard terms and conditions of sale. Parchem does not accept any liability either directly or indirectly for any losses suffered in connection with the use of the product whether or not in accordance with any advice, specification, recommendation or information given by it.

© 2021. This publication is copyright. All rights are reserved. Flextool and the Flextool logo are the trade marks of Parchem Construction Supplies Pty Ltd. Mikasa and the Mikasa logo are the trade marks of Mikasa Sangyo Co. Ltd, used under licence.

HIT HARDER

LAST LONGER

BUILT STRONGER