



## MIKASA RAMMERS

Mikasa 4-stroke and diesel tamping rammers are perfectly balanced to deliver hard hitting compaction while ensuring operator comfort through reduced noise and low handle vibration.

### MTX SERIES FEATURES

- > Reliable 4-stroke engines deliver low emissions and noise
- > Superior four stage air filtration system for engine protection
- > Heavy duty handle mounts reduce operator fatigue
- > Handle roller for easy loading into vehicles
- > Central lifting hook for easy and safe onsite handling
- > Ability to lie down to 90° for transport
- > Side guards for engine protection



MODEL		MTR-40H	MTX-60	MT-65HA	MTX-70	MT-76D
PRODUCT CODE		FT201691-UNIT	FT2TX60E-UNIT	FT2T65HA-UNIT	FT2MTX70-UNIT	FT2MT76D-UNIT
OPERATING WEIGHT	kg	46	64	66	75	82
SHOE SIZE (W X L)	mm	100 x 270	265 x 340	285 x 340	285 x 340	285 x 340
JUMPING STROKE	mm	40-55	50-80	50-80	50-80	50-80
IMPACT RATE	blows/m	644-695	644-695	644-695	644-695	656-698
IMPACT FORCE (MAX)	kN	5.4	13.6	12.7	14.9	15.7
AVERAGE TRAVEL SPEED*	m/min	10-12	10-12	10-12	10-12	10-12
COMPACTION DEPTH*	cm	20-30	50-85	40-65	45-70	50-85
ENGINE MAKE		Honda	Honda	Honda	Honda	Yanmar
ENGINE MODEL		GX100	GX100	GX100	GX100	L48N
MAX RATED POWER	Hp	3	3	3	3	4.7
FUEL TYPE						
FUEL TANK CAPACITY	L	2	2.5	2	3	3.3

## ACCESSORIES

	MTR-40F	MTX-60	MT-65HA	MTX-70	MT-76D
REPLACEMENT SHOE	NPS71383-UNIT	NPS70683-UNIT	NPS70430-UNIT	NPS70430-UNIT	NPS70430-UNIT
TRENCHING SHOE (115mm WIDE x 330 HIGH)	N/A	N/A	NPS51919-UNIT	NPS51919-UNIT	NPS51919-UNIT
TRENCHING SHOE (165mm WIDE x 330 HIGH)	N/A	N/A	NPS51931-UNIT	NPS51931-UNIT	NPS51931-UNIT