

EDGE SERIES CUPWHEELS

Husqvarna Edge grinder tools mirror the logic and performance of the Husqvarna tool system for floor grinders. You can now follow the same steps in your preparation, grinding and polishing process, even for the edges.

Husqvarna SM Edge and HX Edge series have an up to 2.5 times higher removal rate, minimising the time spent on your knees and saving labour cost.


AVAILABLE IN BOTH 125MM AND 180MM DIAMETERS - IN OUR ELITE RANGE

SM CUPWHEELS - LARGER TRIANGLE SEGMENT SHAPES

These are made for **softer floors with a hard bond**, where you still want an acceptable lifetime and the wear is always higher on softer floors than on harder floors - so the segment is larger on SM cupwheels to accommodate for this.

HX CUPWHEELS - SMALLER TRIANGLE SEGMENT SHAPES

These are made for **hard floors with a soft bond**, so these smaller segments avoid pushing too hard on the hand-grinder to keep the segment open. Also as hard floors release less dust, you can use a smaller segment surface area and achieve a similar life.



| EDGE GRINDING SERIES | | | | | | | |
|------------------------|--------------------|--------------|--------------|--------------|--------------|--------------|--------------|
| Part Number - SM 125mm | | 529 85 93-25 | 529 85 91-25 | 529 85 63-25 | 529 85 65-25 | 529 85 66-25 | 529 85 67-25 |
| Part Number - HX 125mm | | 529 85 93-25 | 529 85 91-25 | 529 85 68-25 | 529 85 69-25 | 529 85 70-25 | 529 85 71-25 |
| | MATERIAL | T-REX | PREP 0 | 25 GRIT | 40 GRIT | 80 GRIT | 150 GRIT |
| REMOVE | Glue | ●● | ●● | ● | - | - | - |
| | Residue | ●● | ● | ● | - | - | - |
| | Coatings | ●● | ●● | ● | - | - | - |
| | Leveling compound | ●● | ● | ● | - | - | - |
| | Paint | ●● | ●● | ● | - | - | - |
| | Abrasive Surfaces | ● | ●● | ● | - | - | - |
| PREPARE | Concrete | - | - | ● | ●● | - | - |
| | Aggregate Exposure | - | - | ●● | ● | - | - |
| REFINE | Refining Surface | - | - | - | - | ●● | ●● |
| | Grouting | - | - | - | - | ● | ●● |

●● = Optimal ● = Acceptable

180 MM CUP WHEELS

| | | | |
|--------------|---------------|----------------|---------|
| 529 85 68-80 | HARD CONCRETE | CUPWHEEL 180MM | 25GRIT |
| 529 85 69-80 | HARD CONCRETE | CUPWHEEL 180MM | 40GRIT |
| 529 85 70-80 | HARD CONCRETE | CUPWHEEL 180MM | 80GRIT |
| 529 85 71-80 | HARD CONCRETE | CUPWHEEL 180MM | 150GRIT |
| 529 85 63-80 | SM CONCRETE | CUPWHEEL 180MM | 25GRIT |
| 529 85 65-80 | SM CONCRETE | CUPWHEEL 180MM | 40GRIT |
| 529 85 66-80 | SM CONCRETE | CUPWHEEL 180MM | 80GRIT |
| 529 85 67-80 | SM CONCRETE | CUPWHEEL 180MM | 150GRIT |

180 MM CUP WHEELS

| | | |
|--------------|--------|----------------|
| 529 85 91-80 | PREP 0 | CUPWHEEL 180MM |
| 529 85 93-80 | T-REX | CUPWHEEL 180MM |

Find out More
on Surface
Preparation



husqvarnaconstruction.com/au

Copyright © 2022 Husqvarna AB (publ.) All rights reserved.
Husqvarna is a registered trademark of Husqvarna AB (publ.)