## HUSQVARNA VARI-GRIND G 600 GRINDING DIAMOND SEGMENT

**SEGMENT** 

HEIGHT



A silver level range of metal-bond diamond tools for the Redi Lock® system, providing great work result in all round surface prep applications. Ideal for rental and domestic use. Available in various bond hardness and grit sizes, easily identified by colour and segment shape.

**AVAILABLE IN DOUBLE OR SINGLE SEGMENTS** 







## SINGLE SEGMENT VS DOUBLE SEGMENT

**SINGLE SEGMENT** – More aggressive productivity, reduced tool life. **DOUBLE SEGMENT** – Smoother scratch pattern, improved tool life.

		SOFT BOND - HARD CONCRETE			MEDIUM BOND - MEDIUM CONCRETE			HARD BOND - SOFT CONCRETE	
	VARI-GRIND SERIES								
	Part Number - Singles	503 84 79-02	503 84 79-04	503 84 79-06	503 88 34-01	503 88 34-03	503 88 34-05	503 88 55-01	503 88 55-03
	Part Number - Doubles	503 84 79-03	503 84 79-05	503 84 79-07	503 88 34-02	503 88 34-04	503 88 34-06	503 88 55-02	503 88 55-04
	MATERIAL	20 GRIT SOFT	30 GRIT SOFT	50 GRIT SOFT	20 GRIT MEDIUM	30 GRIT MEDIUM	50 GRIT MEDIUM	20 GRIT HARD	30 GRIT HARD
REMOVE	Contaminant	••	•	-	••	•	-	••	•
	Glue	•	•	_	••	•	_	•	•
	Grout	•	•	_	••	•	-	•	•
PREPARE	Epoxy paint	•	•	_	••	•	_	•	•
	Rain damage	_	_	_	_	_	_	_	••
	Rough concrete	•	•	_	•	•	_	•	••
	Exposing aggregate	•	•	_	•	••	_	•	•
	Exposing aggregate Cleaning concrete	•	•	_	•	••	_	•	•
	Honed finish	_	_	••	_	_	••	_	_
	Grind & seal	-	-	••	-	-	••	-	-

● = Optimal
■ = Acceptable

CAN BE USED DRY OR WET

Move to softer bond when diamonds glaze

Move to harder bond if excessive wear on

## **HUSQVARNA SHARX™**

For fast and easy removal of dense surfaces on hard-troweled concrete floors. The Sharx™ metal bond significantly increases the productivity and ensures that the pads stay opened and sharp even on the hardest top layers.

AVAILABLE IN DOUBLE OR SINGLE SEGMENTS



Find out More on Surface Preparation



## husqvarnaconstruction.com/au

Copyright © 2022 Husqvarna AB (publ.) All rights reserved. Husqvarna is a registered trademark of Husqvarna AB (publ.)