

# SELLEYS®

## PRO-TRADE

### ALL PURPOSE ADHESIVE & SEALANT



A HIGH QUALITY, 100% NEUTRAL SILICONE ADHESIVE & SEALANT, IDEAL FOR MOST COMMON BUILDING SUBSTRATES.

- 100% neutral cure silicone
- Ideal for most common building substrates\*
- Highly flexible +/- 25% joint movement
- Low VOC
- Mould & mildew resistant
- Low slump
- Weather & UV resistant
- Will not corrode metals

\*Pretest on substrates is recommended.

PRODUCT CODE	BARCODE	COLOUR	SIZE	CARTON QTY	LAYER QTY	PALLET QTY
102105	9300697129901	<input type="checkbox"/> CLEAR	300G	12	432	1,728

PROPERTY	TYPICAL RESULT
Technology	Neutral cure silicone
Colour	Clear
Density	1.04
Application Temperature	Minimum 5°C
Skin Time 25°C / 50% RH	4 - 8 minutes
Cure Rate	10mm in 5-7 days
Slump JIS A 1439	No Slump (0.1% max)
Tensile Strength JIS K 6249	2.0 MPa
Shore A Hardness ASTM D2240	28
Elongation at Break JIS K 6249	400%
Movement Capability	+/- 25%
Service Temperature	-60 - 1700C
VOC Content SCAQMD Method 304-91	30 g/L

Indicative data only, not intended for preparation of specifications

IF IT'S SELLEYS IT WORKS®