

SELLEYS®

PRO-TRADE

CONSTRUCTION ADHESIVE MULTIPURPOSE



A HIGH STRENGTH, MULTIPURPOSE ADHESIVE THAT FORMS A STRONG AND LASTING BOND ON MOST BUILDING SUBSTRATES.

- High strength
- Water resistant
- Ideal for most building substrates
- Easily extrudable at low temperatures

PRODUCT CODE	BARCODE	SIZE	CARTON QTY	LAYER QTY	PALLET QTY
102108	9300697129932	320G	20	400	1,600

PROPERTY	TYPICAL RESULT
Technology	Solvent based synthetic rubber
Colour	Beige
Density	1.15
Open Time	20-30 min. (depending upon prevailing conditions)
Initial Cure	Strong bond after 24 hours
Full Cure	7 days
Sag Resistance AS 2329 (1999) Appendix A	Approx. 2mm
Flow and Transfer AS 2329 (1999) Appendix B	> 75% transfer after 15 minutes drying
Initial Bond Strength AS 2329 (1999) Appendix D	> 500 kPa after 24 hours
Bond Strength in Tensile Shear AS 2329 (1999) Appendix E	>1 MPa
Bond Strength in Peel AS 2329 (1999) Appendix F	Approx.40 N/25mm
Static Load in Shear AS 2329 (1999) Appendix G	> 10 days sustaining a 40N load @ 40°C

Indicative data only, not intended for preparation of specifications

IF IT'S SELLEYS IT WORKS®