

# SELLEYS®

## PRO-TRADE

### GAP FILLER SMOOTH FINISH



A HIGH PERFORMANCE, PAINTABLE, FLEXIBLE ACRYLIC GAP SEALANT, SUITABLE FOR INTERIOR AND EXTERIOR APPLICATIONS.

- Paintable with water and oil based paints without the need of priming\*.
- +/-10% Joint movement
- Sag resistant
- Fast clean up with water
- Suitable for use on wood, brick, aluminium, glass, plasterboard, ceramic tiles and painted surfaces

\*Paintable with most water and oil based paint

PRODUCT CODE	BARCODE	COLOUR	SIZE	CARTON QTY	LAYER QTY	PALLET QTY
102106	9300697129918	■ WHITE	475G	20	400	1,600

PROPERTY	TYPICAL RESULT
Technology	Water based acrylic
Colour	White
Density	Approx. 1.58
Application Temperature	Above 5°C
Skin Time 25°C / 50% RH	20 – 30 minutes
Working Time 23°C / 50% RH	30 minutes
Tack Free Time 23°C / 50% RH	60 minutes
Shore A Hardness (DIN 53505)	Greater than 410
Movement Capability ISO 9046	+/- 10%
VOC Content Calculated according to the formula specified in The South Coast Air Quality Management District Rule 1168.	19g/L

Indicative data only, not intended for preparation of specifications

IF IT'S SELLEYS IT WORKS®