

SELLEYS®

PRO-TRADE

JOINT SEALANT LM



NON-SLUMPING POLYURETHANE SEALANT WITH HIGH MOVEMENT CAPABILITY AND EXCELLENT ADHESIVE PROPERTIES

- Weatherproof
- High flexibility with $\pm 25\%$ joint movement
- Cures bubble free
- Sag resistant
- No shrinkage during curing
- Excellent adhesion on common building materials
- Certified according to EN 15651
- Suitable for sealing expansion and construction joints in vertical and horizontal applications

PRODUCT CODE	BARCODE	COLOUR	SIZE	CARTON QTY	LAYER QTY	PALLET QTY
102110	9300697129994	■ WHITE	310ML	12	432	1728
102111	9300697130006	■ GREY	310ml	12	432	1728
102112	9300697130013	■ BLACK	310ml	12	432	1728
102113	9300697130020	■ WHITE	600ml	12	192	960
102114	9300697130037	■ GREY	600ml	12	192	960
102115	9300697130044	■ BLACK	600ml	12	192	960

PROPERTY	TYPICAL RESULT
Technology	Polyurethane
Colour	White, Grey and Black
Density	1.2 \pm 0.03 g/ml
Application Temperature	5°C - 40°C
Tack-Free Time (23°C / 50% RH)	20 - 70 minutes
Cure Rate (23°C / 50% RH)	\geq 2.5 mm/24h
Sagging (EN ISO 7390)	0 mm
Tensile Strength (ASTM D412)	1.5 - 2.0 N/mm ²
Elongation at Break (ASTM D412)	\geq 600%
Shore A Hardness (ASTM C661)	Approx. 35 - 40
Modulus at 100% Elongation (ISO 8339)	0.35 - 0.40 N/mm ²
Movement Capability (EN 15651)	\pm 25%
Service Temperature	- 40°C / +90°C

Indicative data only, not intended for preparation of specifications

IF IT'S SELLEYS IT WORKS®