

SELLEYS®

PRO-TRADE

CROSSLINKING PVA WOOD GLUE



AN INDUSTRIAL-GRADE CROSSLINKING PVA, DEVELOPED FOR USE BY PROFESSIONAL WOODWORKERS AND CRAFTSMEN

- Superior strength and heat resistance
- Interior and exterior use
- Weatherproof
- Excellent water resistance
- Transparent after drying
- Can be sanded, chiselled, routed or turned
- Ideal for dowelling, joinery, laminating, veneering and cabinet & furniture making

PRODUCT CODE	BARCODE	SIZE	CARTON QTY	LAYER QTY	PALLET QTY
102123	9300697129956	500ml	12	288	1152
102124	9300679129963	4L	2	48	192

PROPERTY	TYPICAL RESULT
Technology	Crosslinking PVA
Colour	Applies white, dries clear
Solids Content	49.0 – 51.0%
pH	2.8 – 3.5
Viscosity (Brookfield)	9,000 – 15,000cP at 25°C
Application Temperature	10°C minimum
Clamp Time	Softwoods – 30 minutes Hardwoods – 1 hour
Full Cure	Approx. 24hrs
Water resistance (EN204)	D3

Indicative data only, not intended for preparation of specifications

IF IT'S SELLEYS IT WORKS®