

# MQ WHITEMAN EDGING SERIES WALK-BEHIND POWER TROWEL J3036H55

The MQ Whiteman Edging Series of Walk-Behind Power Trowels are available in 24", 30" and 36" working widths. The quality J3036H55 trowel enables the operator to finish tight to the wall without marking or marring and easily manoeuvre around obstacles. The innovative and patented ABS plastic rotating ring resists concrete build and allows the operator to switch between 30" and 36" working widths, making this a truly versatile machine. Available with both standard pitch or QuickPitch™

Controls for fast and precise blade adjustment.



Convertible edge guard

Change between 30" and 36" operating widths

## PRODUCT & PERFORMANCE SPECIFICATIONS



#### **EDGING SERIES WALK-BEHIND POWER TROWELS**



MQ Whiteman Walk-Behind Power Trowels are supplied **without** a handle. These should be ordered separately.

Model	Trowel Rotor Diameter (mm) (in)	Handle Type (Handles ordered separately)	Operating Weight (kg)	Number of Blades	Speed Range (rpm)	Blade Pitch Max (deg)	Engine Make	Engine Model	Max Rated Power (Hp)	Fuel Type	Product Code (Does not include handle)
СА4НС	610 (24)	STHAC	65.50	4	70-130	30	Honda	GX120	4	ø	FT269000-UNIT
J3036H55	760 (30)	SXH	76.25	4	60-115	30	Honda	GX160	5.5	ð	FT269001-UNIT
	915 (36)	QXH	81.50								

#### HANDLE OPTIONS - ORDERED SEPARATELY

Model	Product Description	Product Code
STHAC	Standard knob style pitch control for CA4HC (centrifugal clutch) model	FT269006-UNIT
SXH	Standard knob style pitch control for J and B Series trowels	FT269007-UNIT
QXH	QuickPitch™ style control for J and B Series trowels	FT269008-UNIT



#### TROWEL BLADES AND PAN FLOATS

Model	Combination Blade	Pan Float		
СА4НС	FT269020-UNIT	FT269029-UNIT		
J3036H55 (30" Configuration)	FT269021-UNIT	FT269030-UNIT		
<b>J3036H55</b> (36" Configuration)	FT269022-UNIT	FT269031-UNIT		

For further information and specifications please refer to the MQ Whiteman Trowel Blades and Pan Floats Technical Data Sheet.

MQ Whiteman products are only available through authorised dealers in Australia. Click here to find your nearest authorised dealer.

### **EXCLUSIVE TO**



This Technical Data Sheet (TDS) summarises our best knowledge of the product, based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used. Our responsibility for products sold is subject to our standard terms and conditions of sale. Parchem does not accept any liability either directly or indirectly for any losses suffered in connection with the use of the product whether or not in accordance with any advice, specification, recommendation or information given by it.