

Bautek JOINTSET is a premium advanced modified jointing sand that consists of selected sands, high performance admixtures and additives. Bautek JOINTSET is used in all types of flexible pavement construction from domestic application through to commercial and civil construction. The formula works by creating a harder stable joint that is not as impervious to joint erosion.



RECOMMENDED FOR

- ✓ Joint widths between 2mm and 4mm
- ✓ All forms of flexible pavement construction
- ✓ Sloping sites
- ✓ Roadways, multi-use pavements and streetscape paving (where designed)
- ✓ In high wind areas

FEATURES

- ✓ Australian designed and made
- ✓ Helps retain integrity and stability of the joints between pavers
- ✓ Resists wash out after 24hrs of setting / curing
- ✓ Retards weed growth
- ✓ Is quick and easy to apply
- ✓ Minimises wind-blown joint erosion

COMPRESSIVE STRENGTH

At 23°C	24hrs 1 MPa	7d 2 MPa	28d 2.5 MPa
Package size	20kg water resistant bags		

PREPARATION & INSTALLATION

- Ensure surface is completely dry before placing JOINTSET.
- Spread JOINTSET evenly over pavement before compacting (plate compactor size and weight will depend on pavement product and thickness).
- Sweep pavement after compaction and ensure all joints are filled evenly and all excess is thoroughly removed from the surface of the pavement.
- Lightly mist pavement so that the moisture absorbs into the surface of the joints. Do not flood initially as it will wash material out and create uneven jointing depths. After the initial misting you can soak the pavement more thoroughly and introduce further moisture through the full depth of the joint.
- The material is a gel setting product. In dry conditions curing will take 1-2 hrs (depending on depth of joint), in cooler conditions curing will take longer. Drainage and permeability of bedding layer and subbase as well as weather conditions will all factor in the length of time to cure/set.

HEALTH & SAFETY

Bautek supports best practice in material handling: Gloves, mask and protective clothing should be worn. Avoid inhalation of dust during mixing and wear safety glasses, dust mask and gloves. If skin contact occurs, wash thoroughly with clean water. Should eye contact occur, rinse immediately with plenty of clean water. Bautek is non-flammable.

For a full SDS on this product contact info@pavementinnovations.com.au

WARRANTY

Bautek warrants this product will perform to its product specification provided that the use and installation of the product has been carried out in accordance with the latest version of the manufacturer's technical instructions and all relevant local council, state, national and international standards as appropriate for the application.

Bautek cannot be held responsible for any product failure, loss or damage arising from incorrect usage or installation, or usage outside the suitability of the product as stipulated in the manufacturer's technical instructions. No discussion will be entered into unless a representative of Bautek is afforded the opportunity to inspect any alleged failure.

To the full extent permitted by the law in Australia and New Zealand, Pavement Innovations Pty Ltd is limited in their discretion to replace or resupply goods.

For further information contact info@pavementinnovations.com.au