

EDGER CONCRETE TROWELS - TOL60G/TOL75G

Dependable Concrete Trowels that you can count on in the toughest conditions. After you float and finish the floor you can then eliminate the laborious hand finishing required along the walls and around any columns. Available in two sizes, our edgers are of simple design but built to take the rough handling of a construction job site and equipment rental use. Both models feature heavy-duty gearboxes and rotating rings that allow the edger to glide smoothly along the wall.



TOL60G

24" (600mm) blade width that works right up against the wall. Use this model for small dimension floors, a perfect companion model to a 36" twin ride-on trowel. A convenient folding handle makes it easier to transport in smaller vehicles and saves space for storage.



TOL75G

For working on those larger projects, use as your 30" (750mm) diameter edger trowel on your larger floors. A rotating guard ring allows you to finish right up against the wall and will give you the smooth finish you require. A convenient folding handle makes it easier to transport in smaller vehicles and saves space for storage.



Folded Handle for Transportation



Rotating Ring



HD Centrifugal Clutch



Gear Box Sight Gauge

Technical Data

DESCRIPTION	TOL60G	TOL75G
DIMENSION-LxWxH - in (mm)	1,510 x 630 x 993	1,520 x 750 x 990
GUARD RING DIAMETER - in (mm)	630	750
OPERATING WEIGHT - lb (kg)	56	64
HANDLE TYPE	FOLDABLE (FULL-FOLD)	FOLDABLE (FULL-FOLD)
FINISHING BLADE SIZE - in (mm)	230 x 120	270 x 120
MAX. BLADE PITCH ANGLE(°)	15	15
BLADE OPERATING SPEED (rpm)	85-138	85-138
ENGINE OPTIONS	HONDA® GX160 @ 3.6kW (4.8hp) 4-Stroke Petrol	HONDA® GX160 @ 3.6kW (4.8hp) 4-Stroke Petrol