G-Force
Ultra 21

PRODUCT DATA SHEET **ITEM CODE: GCU240**

Product Overview

- **Liner Material:** Nylon, Steel, Spandex, Graphene
- **Dip Material:** Nitrile
- **Dipping Style:** Sandy
- **Touch Screen:** Yes
- **MSDS:** N/A
- **Food Contact:** no
- **Cuff Style:** Knit Wrist
- **Gauge:** 21
- **Country of Origin:** China



Applications

- Construction
- Security, Emergency
- Manual Handling
- Glass Handling
- Maintenance
- Metal Handling
- Engineering

Standards and Certification

EN388:2016 +A1:2018 4X43F

EN 16350:2014

REACH COMPLIANCE

Sanitized Actifresh

OEKO TEX® STANDARD 100

Care/Cleaning Instructions

- Cleaning method: hand wash only, clean mild stains with clean water; Gently scrub oil/dust with neutral detergent/mild soapy water
- Water temperature: cold/warm water ≤ 40°C
- Prohibited: bleach, strong acid and strong alkali, strong alkaline laundry detergent, organic solvents (gasoline/acetone)
- Be sure to thoroughly rinse and leave no soap/ detergent residue
- Natural drying in a cool and ventilated place; The lining can be turned outward to accelerate drying. Do not expose to direct sunlight, place over fire, or use a heater/dryer

Storage

- Store in a dry, cool, and well-ventilated area. Temperature 10-25 °C, humidity <60%
- Avoid direct sunlight and ultraviolet rays to prevent aging and brittleness
- Avoid heat: Keep away from heating sources such as stoves, ovens, and open flames
- Store in a sealed bag/storage box to prevent dust and moisture; Do not mix with sharp/ rusty metals
- Storage method: Flat or suspended, avoiding squeezing, excessive folding and pulling.

Manufactured for Maxisafe. A 100% Australian Owned Company.

2025 E&OE

Size Details

Product	Size	Hem Colour
GCU240-07	**S**	White
GCU240-08	**M**	Green
GCU240-09	**L**	Brown
GCU240-10	**XL**	Yellow
GCU240-11	**2XL**	Grey

Packaging

Hangcard: 1 pair
Polybag: 12 pairs
Carton: 120 pairs

Warranty


Limited lifetime – manufacturing defects

Accessories	
Code	Description
GGG115	Maxisafe Glove Clip

Glove and hand size chart as per standard EN ISO 21240									
Glove size	**5**	**6**	**7**	**8**	**9**	**10**	**11**	**12**	**13**
Palm Circumferences	127mm	152mm	178mm	203mm	229mm	254mm	279mm	304mm	329mm
Hand Length	148mm	160mm	171mm	182mm	192mm	204mm	215mm	227mm	237mm
Standard Glove Sizes	XXS/5	XS/6	S/7	M/8	L/9	XL/10	XXL/11	3XL/12	4XL/13
Maxisafe Riggers and Mechanics Glove Sizes	XXS/6	XS/7	S/8	M/9	L/10	XL/11	XXL/12	3XL/13	4XL/14

AS/NZS 2161.3 Occupational protective gloves, Part 3: Protection against mechanical risk

Based on EN388 – Protective gloves against mechanical risks.



EN388:2016
XXXXXX

Abrasion	**1-4**
Cut (Coup Test)	**1-5**
Tear	**1-4**
Puncture	**1-4**
Cut (TDM Test ISO 13997)	**A-F**
Impact Protection	**P,F,X**

Manufactured for Maxisafe. A 100% Australian Owned Company.

2025 E&OE

G-Force
Ultra 21

PRODUCT DATA SHEET
ITEM CODE: GCU240

EN388:2016+A1:2018	Level 1	Level 2	Level 3	Level 4	Level 5
Abrasion resistance (number of cycles)	100	500	2000	8000	-
Blade cut resistance (index)	1.2	2.5	5	10	20
Tear resistance (N)	10	25	50	75	-
Puncture resistance (N)	20	60	100	150	-

EN ISO 13997:1999 TDM	Level A	Level B	Level C	Level D	Level E	Level F
Cut resistant test levels (N)	2	5	10	15	22	30

EN388:2016+A1:2018 IMPACT TEST	P (Pass)	F (Fail)	X
Average transmittance force (kg)	≤ 7kg	≥ 9kg	Not tested